
FOR OPERATION OF SINGLE STEER PICKER TRUCK

STEERING AXLE WEIGHT:

The steering axle weight shall not exceed the lesser of:

1. permitted axle weight
2. the capacity of the steering axle
3. tire capacity based on tire width as stamped on the tire

<u>SIZE</u>	<u>WEIGHT</u>
315 mm	6300 kg
335 mm	6700 kg
365 mm	7300 kg
385 mm	7700 kg
425 mm	8500 kg
445 mm	9100 kg

NOTE: The steering axle weight allowance is for the tare weight of the truck and mounted equipment only.

A payload or commodity, when loaded on the deck of the truck, must be positioned such that no additional weight is placed on the steering axle.

Truck with a fifth wheel must have a pin setting neutral or negative to avoid putting payload weight onto the steering axle.

TRAILERS:

Trailers shall conform to the dimension requirements in the regulations, (wheelbase, overhang, box length, etc.) except when the trailer is exempted by an overdimensional permit.

DIMENSIONS:

The height of the picker shall not exceed 5.0 meters.

The height of the trailers and/or load shall not exceed 4.15 meters.

The maximum overall length of the picker truck and towed semi-trailer shall not exceed 28.0 meters.

GENERAL:

Permission from local, municipal and urban authorities shall be obtained prior to traveling on their roads.