

Excavate minimum of 0.3m below finished gravel surface. Compact exposed surface and restore to grade with compacted fill.

CULVERTS
Where sloped end culverts are used, the 2:1 sloped end is recommended.

EARTH CUT SECTION

- * Width of ditch - 2.0m desirable, "V" ditch minimum.
- * Depth of ditch - 0.6m standard.
- * Backslope variable up to maximum noted.
- * Backslope agreement may be necessary unless additional right-of-way is purchased.

NOTE:

This standard is intended for very short sections of low volume local roads, usually serving a single purpose. These roads will be gravel surfaced. Volume is normally less than 25 AADT. Design speed ranges from 30km/h to 50km/h.


FILL SECTION

- * 3:1 slopes for average fills less than 4.0m.
- * On fills greater than 8.0m, the use of guardrail should be considered.
- * Where guardrail is installed, a 2:1 slope is adequate.

△			
△			
No.	REVISIONS	BY	DATE

Approved:
ORIGINAL SIGNED
BY PETER TAJCNER
.....
Executive Director,
Technical Standards Branch

Date: JULY 3, 1992



OBSOLETE J-4-10
SEE FIGURE

STANDARD CROSS-SECTION
FOR ONE-LANE TWO-WAY
LOCAL ROAD
RLU-104G-50 /40 /30

Prepared By: Cgk	Checked By: BK	Scale: N.T.S.	Dwg No.: CB6-2.3M52
------------------	----------------	---------------	---------------------