



**Part 1 - Dimension Limits**



DIMENSION	LIMIT
<b>Overall Length</b>	Maximum 23.0 m
<b>Overall Width</b>	Maximum 2.6 m
<b>Overall Height</b>	Maximum 4.15 m
<b>Tractor:</b>	
Wheelbase	Maximum 6.2 m
Tandem Axle Spread	Minimum 1.0 m/Maximum 1.85 m
<b>Semi-trailer</b>	
Length	Maximum 16.2 m
Wheelbase	Minimum 6.25 m/Maximum 12.5 m
Kingpin Setback	Maximum 2.0 m radius
Effective Rear Overhang	Maximum 35% of wheelbase
Tandem Axle Spread	Minimum 1.0 m/Maximum 1.85 m
Tridem Axle Spread	Minimum 2.4 m/Maximum 3.7 m
Track Width	Minimum 2.5 m/Maximum 2.6 m
<b>Interaxle Spacings</b>	
Single Axle to Single, Tandem or Tridem Axle	Minimum 3.0 m
Tandem Axle to Tandem Axle	Minimum 5.0 m
Tandem Axle to Tridem Axle	Minimum 5.5 m

**Part 2 - Weight Limits**



WEIGHT	LIMIT
<b>Axle Weights:</b>	
<b>Steering Axle</b>	Maximum 6000 kg
<b>Carrying Axles:</b>	
<b>Single Axle</b>	
Single tires	Maximum 7300 kg
Wide base single tires	Maximum 9100 kg
Dual tires	Maximum 9100 kg
<b>Tandem Axle</b>	
Single tires	Maximum 13,600 kg
Wide base single tires	Maximum 17,000 kg
Dual tires	Maximum 17,000 kg
<b>Tridem Axle</b>	
Single tires	Maximum 19,000 kg
Dual and wide base single tires with axle spread from 2.4 m to less than 3.0 m	Maximum 21,000 kg
Dual and wide base single tires with axle spread from 3.0 m to 3.7 m	Maximum 24,000 kg
<b>Gross Vehicle Weight Limits</b>	
See Weight Calculator <a href="https://www.alberta.ca/commercial-vehicle-weight-and-dimensions-regulations.aspx">https://www.alberta.ca/commercial-vehicle-weight-and-dimensions-regulations.aspx</a>	Cannot exceed the sum of the maximum legal axle weights and is subject to minimum interaxle spacing.

All axle weights are subject to minimum tire size. The maximum weight per tire shall not exceed the lesser of the tire manufacturer's weight rating or the width of the tire stamped on the sidewall multiplied by 10 kg/mm.